

QUADROFLEX

Flexible rectangular duct



Ordered to customer order, limited stock.

Note that delivery time is normally up to 4 weeks because it is not a stock item.

QUADROFLEX

Description

The folding technique means that the duct is durable and user-friendly, and reduces weight by up to 50% compared to steel sheet ducts. Quadroflex is a flexible duct and can be turned 90 degrees and the ends adapted to the relevant coupling diameter. Transition and/or coupling parts can be manufactured for all profile shapes.

Area of use

Quadroflex is for ventilation, smoke/gas, preheating, defroster and electronics and is therefore suitable for use in: *Factories, houses, cars, boats and trains*

Material

Single layer of profiled strips, corrugate and fold together. The most common material is aluminium or galvanised steel strips.

Properties

A flexible duct that is suitable for confined spaces. Installation requires no extra tools.

Cut using a knife

Temperature range

+ 200°C

Dimensions

See table below, standard length is 3m.

Bend radius

Can be turned up to 90 degrees

Fire classification

Non-flammable

Approval

Pressure drop diagram available in a separate catalogue

Accessory

See pages 18-20 for accessories for Quadro-products.

Dimensions table

Internal dimension (mm)	System	Standard length
129x52	100	3m
158x70	125	3m
192x80	150	3m
271x80	200	3m